

PS Audio cjenik 01.03.2010.



POWER CONDITIONERS

MPC/kn

Power Plant Premier

AC power regenerator, produces regulated, pure 120 volt AC for all components. Multiwave and Cleanwave, 10 AC receptacles, 5 IsoZones, Over/Under voltage + surge and spike protection, 12 volt trigger, sequential turn on, Coax and Phone protection. Available in Silver or Black.



13.980 kn (AKCIJA)

PowerPlay IPC-9000

Network controllable power conditioner. 10 separate zones. Touch panel. Reboot any device from anywhere in the world. Send IR commands. Fully customizable. Automatically corrects network problems with zero intervention. Phone control for backup.



11.680 kn

PowerPlay IPC-8000

Network controllable power conditioner. 3 separate zones. Reboot any device from anywhere in the world. Send IR commands. Fully customizable. Automatically corrects network problems with zero intervention. No network setup needed.



7.780 kn

PowerPlay UPS 1500mkII

Companion Uninterruptable Power Supply. 1500va communicates through PowerPlay device reporting battery life, status & activation. Easy swap batteries. Pure Sine Wave output. PS link for PowerPlay communication. Voltage regulation.



7.780 kn

Power Center AV-5000

Audio Video Power Control Center. 10 outlets featuring individual control IR and RS-232 control, 5 Isozones. Send IR commands. Fully customizable. Automatically corrects network problems with zero intervention.



7.980 kn

Power Center AV-3000








Audio Video Power Control Center. 3 separate Isozones with IR and RS232 based control. Send IR commands. Fully customizable. Automatically corrects network problems with zero intervention.



4.980 kn





PS Audio cjenik 01.03.2010.



POWER CONDITIONERS	MPC/kn
<p>Quintet AC surge & spike protection, conditioning and distribution component strip. 10 AC receptacles, 5 IsoZones, Over/Under voltage + surge and spike protection, 12 volt trigger, sequential turn on, Coax and Phone protection. No power restriction.</p>	 <p>2.880 kn</p>
<p>Duet AC surge & spike protection, conditioning and distribution component strip. 4 AC receptacles, 2 IsoZones, Over/Under voltage surge and spike protection, No power restriction.</p>	 <p>1.580 kn</p>
<p>Juice Bar II The world's finest power extension strip. No circuitry to alter current delivery. Pure Copper buss bars connected directly to the IEC and each of the 4 Power Ports. Creates a star ground and eliminates ground loop induced noise.</p>	 <p>1.480 kn</p>
<p>Soloist Special Edition The world's best in-wall power conditioner and spike protector. In-wall HC Ultimate Outlet with Power Port Premier, Cleans and protects, Spike protection, Unrestricted dynamics Easy to install, Safe, ETL certified.</p>	 <p>1.980 kn</p>
<p>Soloist The world's first in-wall power conditioner and spike protector. In-wall HC Ultimate Outlet, Cleans and protects, Spike protection, Unrestricted dynamics Easy to install, Safe, ETL certified.</p>	 <p>1.580 kn</p>
<p>Humbuster III Eliminates DC offset, reducing induced transformer hum. No filtration, no protection. The Humbuster III is the only product which can eliminate the nasty mechanical buzz from your gear's power transformer.</p>	 <p>2.380 kn</p>
<p>Noise Harvester - Black or White Converts line noise to light Works at frequencies 10 times lower than other filters.</p>	 <p>780 kn (3.240 kn > 5 kom.)</p>

PS Audio cjenik 01.03.2010.



AUDIO COMPONENTS		MPC/kn
<p>PerfectWave DAC (PWD) State-of-the-art network D to A processor . Full color touch screen control, 6 digital inputs, 24/96 USB capable, I2S through HDMI, Native resolution, upsample capability from 44.1kHz through 192kHz, volume control, phase control. Included IR remote, Silver or Black</p>		22.490 kn
<p>PerfectWave Transport (PWT) State-of-the-art network capable optical disc transport. Full color touch screen control, reads Redbook CD as well as wav files on DVD, I2S through HDMI, 440,000 gate FPGA engine, HRx and high resolution audio files up to 24 bit 192kHz. Included IR remote, Silver or Black</p>		22.490 kn
<p>Digital Link III DAC The DL III is the sweetest sounding DAC anywhere, incredible price point. Accepts USB, Toslink and coax S/P- DIF with single ended and true differential (balanced) outputs, 24/96-192 upsampling, all discrete pure class A output circuitry. 8.5"w x 3"h x 15.5"d</p>		5.380 kn
<p>GCPH Phono Stage The GCPH is the finest phono stage we have ever made in our 30 year history of building high end phono stages. Awesome musicality, open, spacious sound. Accepts any cartridge, moving coil or moving magnet. Extremely low noise. 8.5"w x 3"h x 15.5"d</p>		7.380 kn
<p>The Bridge Optional network for PWD, May 2010</p>		cca 4.000 kn
<p>The NAS PerfectWave network storage library for PWD, May 2010</p>		cca 14.900 kn

PS Audio cjenik 01.03.2010.



POWER ACCESSORIES

MPC/kn

Power Port Premier

Custom built, hand crafted 15 to 20 amp AC receptacle of the highest quality. The internal contacts are machined out of pure copper, polished and then direct gold plated. Hospital Grade, UL approved, Isolated Ground, easy to install.



680 kn (2.880 > 5 kom.)

Power Port Classic

AC receptacle. 15 coats of nickel plating and polishing. Improved grip strength. Hospital Grade, UL approved, Isolated Ground, easy to install. Improves AV performance and provides years of proper connectivity.



340 kn (1.440 > 5 kom.)

Power Port Designer White

AC receptacle. 15 coats of nickel plating and polishing. Improved grip strength. Hospital Grade, UL approved, easy to install. Improves AV performance and provides years of proper connectivity.



340 kn (1.440 > 5 kom.)

Critical Link

The world's best sounding fuses! Gold plated OFC end caps, OFC element, foam insulation and ceramic body eliminates vibration, Cryogenically treated 5x20mm Type T - Slow Blow

Available in 500mA, 800mA, 1A, 1.6A, 2A, 2.5A, 3.15A, 4A, 5A, 6.3A, 8A, and 10A values.



220 kn

Rack Mount Kit

Attaches the Quintet, Duet, Juice Bar II or Humbuster III to the back of an AV rack, cabinet or directly to your wall.



380 kn

PS Audio cjenik 01.03.2010.



POWER CABLES

MPC/kn

PerfectWave AC-12

Our best AC power cable. 8 gauge, PCOCC Pure Single Crystal Copper Solid Core Conductors. Gold plated and polished connectors. Hermetically sealed, hot & cold welded construction. Multiple shields for ultimate noise rejection.



0.5 m: 4.680 kn
 1.0 m: 5.780 kn
 1.5 m: 6.580 kn
 2.0 m: 7.680 kn
 3.0 m: 9.980 kn

PerfectWave AC-10

10 gauge, PCOCC Pure Single Crystal Copper Solid Core Conductors. Gold plated and polished connectors. Hermetically sealed, hot & cold welded construction. Shielded for noise rejection.



0.5 m: 3.680 kn
 1.0 m: 4.080 kn
 1.5 m: 4.880 kn
 2.0 m: 5.680 kn
 3.0 m: 7.280 kn

PerfectWave AC-5

10 gauge OFC High Purity Copper Solid Core Conductors. Hermetically sealed, hot & cold welded construction. Shielded for noise rejection.



0.5 m: 1.380 kn
 1.0 m: 1.680 kn
 1.5 m: 1.980 kn
 2.0 m: 2.280 kn
 3.0 m: 2.980 kn

PerfectWave AC-3

12 gauge OFC High Purity Copper Solid Core Conductors, Hermetically sealed, hot & cold welded connectors. Shielded for noise rejection.



0.5 m: 680 kn
 1.0 m: 880 kn
 1.5 m: 1.080 kn
 2.0 m: 1.480 kn
 3.0 m: 1.980 kn

xStream Power™ Plasma Cable

Right angle male AC power cable. 12 gauge Multi strand copper conductors, connectors machined from solid billet, nickel plated and polished, shielded, removable ground pin, ferrite impregnated jacket, IEC female.



1.0 m: 480 kn
 1.5 m: 580 kn

Jewel AC Power Cable

AC power cable. IEC or C7 female connectors, standard male. 12 gauge Multi strand oxygen free copper conductors, connectors machined from solid billet, nickel plated and polished, shielded, removable ground pin, ferrite impregnated jacket.



0.5 m: 360 kn
 1.0 m: 420 kn
 1.5 m: 490 kn
 2.0 m: 560 kn
 3.0 m: 720 kn

PS Audio cjenik 01.03.2010.



AUDIO CABLES

MPC/kn

PerfectWave Digital I2S - 10

World's only HDMI cable specially tuned for I2S delivery.
Silver Plated PCOCC Conductors, Tripple Shielded,
Nitrogen Injected Skin-Foam-Skin Dielectric, 24K Gold
Plated Connectors, Non-Ferrous Die Cast Metal
Connector Shells.



0.5 m: 1.080 kn
1.0 m: 1.380 kn
2.0 m: 1.980 kn
3.0 m: 2.580 kn

PerfectWave Digital I2S - 12

World's only HDMI cable specially tuned for I2S delivery.
Highest Purity Solid Silver Core Conductors, Tripple
Shielded, Nitrogen Injected Skin-Foam-Skin Dielectric,
24K Gold Plated Connectors, Non-Ferrous Die Cast Metal
Connector Shells.



0.5 m: 2.680 kn
1.0 m: 3.380 kn
2.0 m: 4.880 kn
3.0 m: 6.580 kn